

Part Number: 6T00UP

Audio Cable, 2 Conductor 10 AWG BC, CL2P



Product Description

Commercial Audio Cable, 2 Conductor 10 AWG highly flexible stranded (65x28) bare copper conductors with Flamarrest® insulation, CL2P, Flamarrest® jacket with ripcord.

Technical Specifications

Product Overview

Environmental Space:	Indoor - Plenum

Physical Characteristics (Overall)

Condu	ctor		
AWG	Stranding	Material	No. of Conductors
10	65x28	BC - Bare Copper	2
Conductor Count:			
Conductor Size:			

Insulation

Material	Material Trade Name	Nominal Wall Thickness
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.011 in

Color Chart

Number	Color
1	Black
2	White

Outer Shield Material

Material Unshielded

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Ripcord
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.302 in	0.017 in	Yes

Construction and Dimensions

Cabling

Lay Direction	Twists
Left Hand	2.82 twist/ft

Electrical Characteristics

Conductor DCR	
Nominal Conductor DCR	
1.07 Ohm/1000ft	
Capacitance	
Nom. Capacitance Condu	ctor to Conductor
28 pF/ft	

Shielding:

Inductance

Nominal Inductance

0.14 µH/ft

Current



Voltage

UL Voltage Rating 150 V RMS

Temperature Range

Operating Temp Range:	-20°C To +75°C
-----------------------	----------------

Multiple or Specialty

Mechanical Characteristics

Bulk Cable Weight:	81 lbs/1000ft
Max Recommended Pulling Tension:	260 lbs
Min Bend Radius/Minor Axis:	3.1 in

Standards

NEC Articles:	725
NEC/(UL) Specification:	CL2P
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No

Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262
CSA Flammability:	FT6
UL voltage rating:	150 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	Vee
Pienum (T/N).	Yes

Part Number

Non-Plenum Number:

5T00UP

Variants

Item # Color

6T00UP 0091000 White

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.